

Product Data Sheet

BOOSTER - T500



Booster	Box Qty (1.1D)	Gross Weight
T500	48	25kgs
Box Dimensions		
40 (L) x 27 (W) x 32 (H) cm		

Description

Suitable for use in quarrying as a bottom hole primer or as a separate charge in opencast mining and seismic operations. Designed to accept two standard detonators, complete with a through centre hole to facilitate ease of sinking and threading of both detonator tails.

Tested in water pressures of 3bar for a 48 hour period, TNT boosters maintain their VOD and sensitivity in wet holes.



Application

TNT boosters are used for the reliable initiation of insensitive explosives such as ANFO, Slurries & Emulsions in package or bulk form.

Apertures

Hole Type	Diameter Ø	Length
Detonator x 2	8mm ±0.5	108mm ±0.5
Centre	12mm ±0.5	Full Length

Recommendations

Products for reliable initiation:

- *DTH Non Electric Detonators
- *Electric Detonators
- *Electronic & Seismic Detonators

Safety & Storage

Explosives should be handled by trained, authorised persons only. Avoid damage to any part of the component and ensure care is taken to protected from extreme impacts, friction & heat sources. "DO NOT" attempt to de-construct products which may cause premature detonation.

Boosters should be kept separate from detonators & initiation articles in a cool, dry, well ventilated licensed magazine when not in use. Stored in typical conditions, boosters have a 10 year shelf life from the date of manufacture. Stocks should be frequently rotated in order to use the older products before the new.

Booster Dimensions

Diameter Ø	60mm ± 1
Length	117mm ± 1
Weight	500g
Box Quantity	48

Technical

Colour	Red - Outer Sleeve
VOD	6800m/s approx
Mass	500g ±20g
Density	1.5g/cm ³
Sensitivity - Impact / Friction	14.7J / >353N

Product Classification

Shipping Name	BOOSTERS without detonator
UN #	0042
Classification	1.1D
EC Type Certificate	3748/01
Notified Body	0589
Packing Group	PGII

BREXCO and partners disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries including death, losses or damages to persons or property arising from the use of this product. Under no circumstances shall BREXCO or any partners be liable for special, consequential or incidental damages or for anticipated loss of profits. E&OE

