

Connecting Wire

Suitable for connecting electric detonators in surface and underground operations.



WIRE SPECIFICATION

INSULATION	MATERIAL	PVC or PE					
	COLOUR	RED					
WIRES		SINGLE			DUPLEX		
	DIAMETER (MM)	1.30 – 1.60			1.40 – 1.60 x 3.00 – 3.40		
CORE	MATERIAL	Cu		Fe / Cu	Cu		Fe / Cu
	DIAMETER (MM)	0.60	0.80	0.65	2x 0.60 (+)	2x 0.80	2x 0.65
RESISTANCE MAX (OHMS)	Ω / 100M	6.40	3.60	40.00	2x 6.40	2x 3.60	2x 40.00

- Temperature Range: -30°C to +60°C
- Mechanical & Electrical compliance standard CSN EN13 763
- Stock (+)

PACKING

WIRES	SINGLE			DUPLEX			Box contents (spools)	Outer box dims (mm)	Plastic spool dims (mm)
	Cu	0.80	Fe/Cu	Cu	Fe/Cu	Fe/Cu			
Dia \emptyset	0.60	0.80	0.65	2x 0.60	2x 0.80	2x 0.65			
Spool Sizes (m)	100	90	100	50	40	45	72	440x270x330	\emptyset 65 x 73
	500	400	500	250	200	200	15	580x360x155	\emptyset 110 x 135
	1000	800	1000	500	400	400	6	440x270x330	\emptyset 150 x 142
	1500	1500	1500	800	700	800	3	440x270x330	\emptyset 230 x 122